

What's new for MARK Basic family

Technical detail



v.s. old models

Use cases

Range

STANDAR RANGE

10 cm - 90 cm / 4" - 35"
LED dot aiming

MID RANGE

30 cm - 150 cm / 4" - 35"
Laser aiming

MULTI RANGE

10 cm - 250 cm / 4" - 98"
Laser aiming

Enhanced scanning flexibility

Workers can quickly scan locations from the vehicle at up to 250 cm / 98"

Ruggedness

2000 tumbles from 0.5m
IP54

Enhanced defense against dust and water splashes from any direction

Battery

8,000 scans*
2h charging time

14% increase - a full shift in high-frequency scanning use cases

Dimensions

50 x 45 x 17 mm
/ 1.47 x 1.77 x 0.67 in
39g/1.38 oz

Temperature

0°C - 50°C /
32°F - 122°F

Guidance

Optic, acoustic, haptic feedback


Sensor

Scan events,
Movement,
Device metadata

Connectivity

BLE,
ProGlove INSIGHT

MULTI RANGE



- Picking for supermarkets with pallet truck / autonomous pallet truck
- Inbound
- Milk-run
- Supermarket
- Staging of materials
- Sorting

STANDARD RANGE MID RANGE



- Stock placement
- Palletizing
- Picking
- Packaging
- Inventory
- Checkout

*Battery life and barcode readability depends on device settings, usage, and many other factors.